

# ▶ INTUGRID VAA22 ◀

## REMOTE INPUT MIXING PANEL




### CONCEPT

The INTUPAK™ VAA22 is the smallest and most unobtrusive solution to audio connectivity and preamplification in any room, fitting into a standard BS5733 wall box offering flush or surface mount options. It offers three audio sources, starting with a 3.5mm stereo TRS input, complemented by a Linkoustic™ wireless audio link input, and completed by a microphone input. All sources can be mixed at the desired ratio, and the master volume can be set by a large dial. The microphone input offers extra versatility with its on/off switch, tone control and adjustable talkover (priority) feature, allowing to automatically attenuate the program material when speaking into the microphone. The VAA22 is highly configurable via internal jumpers for Mic gain, Mic HPF, Mic phantom power and Master stereo/mono settings. The VAA22 does not include any internal power supply and is recommended to be combined with the Intusonic™ SPA22 remote power supply station.

### FEATURES

- ▶ 3 Inputs: Microphone (locking female XLR), Line (3.5mm TRS), Linkoustic Wireless
- ▶ On/off switch, tone control and adjustable talkover for microphone input
- ▶ Individual source / master volume controls
- ▶ Balanced stereo or mono output via 3.5mm terminal strips
- ▶ Configurable Mic Gain, Mic HPF, Mic Phantom Power and Main stereo/mono settings
- ▶ Stand-alone or linked operation as frontend to IntuGrid™ wall panels
- ▶ 86x86mm standard size with BS5733-compliant mounting points
- ▶ Single-gang BS5733 wall box (white) supplied with the product
- ▶ Power supply not included; recommended PSU Intusonic SPA22
- ▶ CE/ROHS compliant



REAR VIEW

### TECHNICAL DATA

|                                     |                             |
|-------------------------------------|-----------------------------|
| Input Sensitivity.....              | Mic -50/-40/-30dB, Line 0dB |
| Residual Noise (Line, Mic Off)..... | -95dBu                      |
| Residual Noise (Mic On).....        | -65dBu                      |
| THD (Line).....                     | 0.02%                       |
| Power requirement.....              | +12V/2x70mA (1.7W)          |
| Dimensions WxDxH.....               | 86x86x40 mm (w knob)        |
| Mounting depth.....                 | 27 mm                       |
| Mounting Standard.....              | BS5733                      |
| Weight.....                         | 0.15kg                      |

### LOGISTICS DATA

|                                    |               |
|------------------------------------|---------------|
| Order Number.....                  | 2023201       |
| Single unit EAN-13.....            | 5060502923554 |
| Single Carton (SC) size WxDxH..... | 103x103x80mm  |
| SC gross weight.....               | 0.2 kg        |
| Units per master carton (MC).....  | 8             |
| MC size WxDxH.....                 | 220x220x180mm |
| MC gross weight.....               | 2.6 kg        |